OIL AND GAS CONSERVATION DIVISION PO Box 171 Oklahoma City, OK 73101 405-521-2331 ogadmin@occ.ok.gov



BACK PRESSURE TEST FOR NATURAL GAS WELLS

TEST:		INITIAL ANNUAL						0	AC 165:10)-17-6								
		RETEST							DA	TE OI	F TEST:				DATE OF	F 1 ST SAL	ES:	
Operator															Operato	or#		
Address												City			ST	ZII	P	
E-mail								Ph				Fax			Well Name/#			
Gas Volu												Gas Volu			API#			
Reported Producing		CC by:										Reporter	· #		OTC			
Zone										ı		_	ı		Lease #			
Surface Location					1/4	1.	/4	1/4	1/4	Sec		Twp	F	Rge .	(OCC us Allowab			
Zone Locati (if differer					1/4	1.	/4	1/4	1/4	Sec		Twp	F	lge .	County			
Field	,									•		•	<u> </u>		Spacing) Size		
COMPLE	101	N:	Single			Multiple	e Zone		Com	nming	led	Red	comple	tion Da	te of Com	pletion		
Total Depth	1			Plug	Back De	oth		-			Packer Se	t Depth			Elevation	1		
Csg Size				WT			d				Depth Se	et			Perfs.			
Tbg Size				WT			d				Depth Se	et			Perfs.			
Prod. Thru				Res.	Temp.	F	•	@)		Mean Gr	d. Temp. F			Atm. Pre	ss. PSIA		
L		Н	G_g		%CO ₂	2		$%N_2$		H ₂ S(p	opm)	Prov	er	Met	er Run		Taps	
SHU	Γ-IN [DATA		DDOVED.		FLO\	N DATA		DIEE			TUBIN	G DATA	CASIN	G DATA	ВНЕ	P DATA	
			LINE	PROVER	ORIF	FICE PRES		DIFF S (INCHE		S)	TEMP	PRESS	TEM	P PRESS	TEMP	PRESS	S TEMP	FLOW (HRS)
PRESS	6	(HRS)	SIZE	Х	SIZ	_	(PSIG)		(ROOT		(F)	(PSIG)	(F)	(PSIG)	(F)	(PSIG)		(FIRO)
					8			RATE	E OF FLO	W CA	LCULAT	IONS	ı		1	I	1	
COE	FFIC	IENT (24 H	HOUR)	$\sqrt{h_w P_n}$	- n		SURE	FLO	W TEMP. F _t	FACT	OR	GRAVITY F F _g	ACTOF		COMPRE	SS	RATE OF (Q) M	
							m		- t			· g		17	CTORT pv		(Q) IVI	CFD
F)		TEMP. R	T,			Z			Gas/l	iquid Hy	drocarbon F	Patio					MCF/BBL
'	r		I LIVII . IX	'1			_					Liquid Hydr		ne				Deg.
										Spec	ific Gravi	ty	0001001		Specific (Deg.
										Sepa Critic	rator Gas al	8		PSIA	Flowing F Critical	Fluid		DOIA
P _c			(PSIA)	P _c ²						Press Critic					Pressure Critical			PSIA
' c			(I SIA)	P _c							erature			R	Tempera	ture		R
Р	w		P _w ²	P _c ² - P	2													
	**		- w		w													
									n							n		
	$P_c^{\ 2}$	=						P _c ²							P _c ²] =		
[1] P	² - P,	2 w	(Not to e	xceed 5.26	63)	[2]	l P	c ² - P _w	2	= .			WHAOF	=Q [P _c ² - P _w ²]		
Calculated	wellh	ead open f	low					MCFE	0 @ 14.65			Angle of S	Slope		Slop	oe, n		
Remarks																		
Approved b	у Со	mmission:		Cone	ducted	by:					Calculate	ed by:			Checked	by:		
WITNESS	ED	- OCC FII	ELD STAFF:	Y] N		NAM	ЛЕ:							DATE:			

IF THE ALLOWABLE FOR THIS WELL HAS BEEN ADJUSTED BY COMMISSION ORDER, PLEASE GIVE THE ORDER NUMBER(S) IN ONE OR MORE OF THE CATEGORIES BELOW:

INCREASE	D DENSITY	LOCATION EXCEPTION	ON
COMMING	LING	MULTIPLE ZONE	
SEPARATE	OR SPECIAL ALLOWABLE *		
OTHER PE	ENALTY ORDER(S) *		
* FOR THE	ESE ORDER TYPES, PLEASE DESCRIBE ALLOWA	ABLES AND/OR PENALTIES:	
which v correct	re that I have knowledge of the contents of this repowas prepared by me or under my supervision and diand complete to the best of my knowledge and beli	rection, with the data and facts statef.	
SIGNA	TURE	TITLE	
COMP		DATE	PHONE NO.
		DATE -IN MINIMUM OF 24 HOURS). RRESPONDING TO THE FLOWING	G WELLHEAD PRESSURE,
COMP.	SHUT-IN PRESSURE, PSIA (LENGTH OF SHUT	DATE T-IN MINIMUM OF 24 HOURS). RRESPONDING TO THE FLOWING OW RATE.) THE VALUE OF PW S	G WELLHEAD PRESSURE,
Pc Pw	SHUT-IN PRESSURE, PSIA (LENGTH OF SHUT STATIC COLUMN WELLHEAD PRESSURE COR PSIA (TO BE RECORDED AT END OF EACH FL	DATE T-IN MINIMUM OF 24 HOURS). RRESPONDING TO THE FLOWING OW RATE.) THE VALUE OF PW S E = 1.000).	G WELLHEAD PRESSURE, SHOULD NOT EXCEED 90% OF Pc.
Pc Pw Gg	SHUT-IN PRESSURE, PSIA (LENGTH OF SHUT STATIC COLUMN WELLHEAD PRESSURE COP PSIA (TO BE RECORDED AT END OF EACH FL SPECIFIC GRAVITY OF SEPARATOR GAS (AIR LENGTH OF THE FLOW STRING FROM THE M	DATE T-IN MINIMUM OF 24 HOURS). RRESPONDING TO THE FLOWING OW RATE.) THE VALUE OF PW S E = 1.000). IDDLE OF THE PRODUCING FOR	G WELLHEAD PRESSURE, SHOULD NOT EXCEED 90% OF Pc.
Pc Pw Gg L	SHUT-IN PRESSURE, PSIA (LENGTH OF SHUT STATIC COLUMN WELLHEAD PRESSURE COF PSIA (TO BE RECORDED AT END OF EACH FL SPECIFIC GRAVITY OF SEPARATOR GAS (AIR LENGTH OF THE FLOW STRING FROM THE M AT WELLHEAD, FEET.	DATE T-IN MINIMUM OF 24 HOURS). RRESPONDING TO THE FLOWING OW RATE.) THE VALUE OF PW S E = 1.000). IDDLE OF THE PRODUCING FOR	G WELLHEAD PRESSURE, SHOULD NOT EXCEED 90% OF Pc.
Pc Pw Gg L	SHUT-IN PRESSURE, PSIA (LENGTH OF SHUT STATIC COLUMN WELLHEAD PRESSURE COP PSIA (TO BE RECORDED AT END OF EACH FL SPECIFIC GRAVITY OF SEPARATOR GAS (AIR LENGTH OF THE FLOW STRING FROM THE M AT WELLHEAD, FEET. VERTICAL DEPTH CORRESPONDING TO L, FE	DATE T-IN MINIMUM OF 24 HOURS). RRESPONDING TO THE FLOWING OW RATE.) THE VALUE OF PW S E = 1.000). IDDLE OF THE PRODUCING FOR	G WELLHEAD PRESSURE, SHOULD NOT EXCEED 90% OF Pc.
Pc Pw Gg L H	SHUT-IN PRESSURE, PSIA (LENGTH OF SHUT STATIC COLUMN WELLHEAD PRESSURE COF PSIA (TO BE RECORDED AT END OF EACH FL SPECIFIC GRAVITY OF SEPARATOR GAS (AIR LENGTH OF THE FLOW STRING FROM THE M AT WELLHEAD, FEET. VERTICAL DEPTH CORRESPONDING TO L, FE 24 HOUR RATE OF FLOW, MCF/D.	DATE T-IN MINIMUM OF 24 HOURS). RRESPONDING TO THE FLOWING OW RATE.) THE VALUE OF PW S E = 1.000). IDDLE OF THE PRODUCING FOR	G WELLHEAD PRESSURE, SHOULD NOT EXCEED 90% OF Pc.
Pc Pw Gg L H Q	SHUT-IN PRESSURE, PSIA (LENGTH OF SHUT STATIC COLUMN WELLHEAD PRESSURE COF PSIA (TO BE RECORDED AT END OF EACH FL SPECIFIC GRAVITY OF SEPARATOR GAS (AIR LENGTH OF THE FLOW STRING FROM THE M AT WELLHEAD, FEET. VERTICAL DEPTH CORRESPONDING TO L, FE 24 HOUR RATE OF FLOW, MCF/D. INSIDE DIAMETER, INCHES.	DATE T-IN MINIMUM OF 24 HOURS). RRESPONDING TO THE FLOWING OW RATE.) THE VALUE OF PW S E = 1.000). IDDLE OF THE PRODUCING FOR	G WELLHEAD PRESSURE, SHOULD NOT EXCEED 90% OF Pc.

Ζ

COMPRESSIBILITY FACTOR, DIMENSIONLESS.