

Lower Washita Planning Region

Summary


- Lower Washita Region demands are supplied by a combination of surface water, groundwater, and out-of-basin supplies.
- Water demand (withdrawal) is projected to increase by 2,965 acre-feet per year (5%) between 2020 and 2075.
- Physical water shortages are projected for surface water and groundwater as early as 2030 and will continue through 2075.
- Surface water and groundwater are projected to remain legally available for permitting through 2075 in all Lower Washita Region basins. Permitting of surface water in portions or all of each of the Lower Washita Region basins is subject to provisions of the 2016 Water Settlement Agreement.
- In addition to the Statewide Recommendations, Lower Washita Region stakeholders expressed the need to consider conjunctive water management, reforming crop insurance, and investing in irrigation districts.



OWRB Water
Planning Page

oklahoma.gov/owrb/water-planning

The Lower Washita Region represents 5% of the state's 2075 projected population and 3% of the state's total 2075 water demand projections.



Reliable water supplies must be physically available (wet water available at the time and place it's needed), legally available (having a permit to use the water), of suitable quality for its intended purpose, and have the necessary infrastructure to divert, convey, and treat the water if necessary. For the Lower Washita Region, to mitigate projected water supply shortages, the following strategies will typically be most effective:

- Reduce water demand through conservation, water loss reduction, and other activities (PS, SSI, OG, TE). **WSS**
- Reduce water demand through agricultural water saving options (CI, LS). **WSS**
- Continue/increase reliance on in-basin surface water (all sectors) in some basins. **WSS** **WDI**
- Continue/increase reliance on in-basin groundwater (all sectors) in some basins. **WSS** **WDI**
- For some basins where existing and traditional strategies are unable to meet future demands, stormwater capture and use (PS, SSI), water reuse (PS, SSI), and water transfers (all sectors) may be effective. **WM** **WSS**

Options to address water quality concerns include expanding source water protection programs and expanding water quality studies. **WSS** **WDI**

Infrastructure limitations can be addressed through additional water funding. Possible sources of new funding include providers setting appropriate water rates, public-private partnerships, state programs, and federal programs. **WIW**

Water Demand Sectors: PS = Public Supply, SSI = Self-supplied Industrial, OG = Oil & Gas, TE = Thermoelectric Power, CI = Crop Irrigation, LS = Livestock, SSD = Self-supplied Domestic

OCWP Statewide Recommendations: The recommendations are designed to address current and anticipated water supply challenges. Areas where the OCWP Statewide Recommendations specifically address this region's challenges are noted throughout this fact sheet with the following icons: **WIW** Water Infrastructure & Workforce, **WM** Water Management, **WSS** Water Supplies & Storage, and **WDI** Water Data & Information



OKLAHOMA
Water Resources Board


Population

2020	2030	2035	2045	2060	2075
226,688	231,991	230,809	229,131	229,989	230,157

Water Demand Projections

Water demands (withdrawals) are projected to increase by 5% between 2020 and 2075.

The Lower Washita Region’s largest demand sector is Public Supply, representing 53% of the region’s 2075 water demands. The second largest demand sector is Crop Irrigation, representing 20% of the region’s 2075 water demands.



Water demand refers to the amount of water that needs to be withdrawn from surface waters and/or groundwater to meet the needs of people, communities, industry, agriculture, and other users. Changes in water demands correspond to growth or decline in population, agriculture, industry, or related economic activity. Demands were projected through 2075 for seven distinct consumptive water demand sectors.

In the Lower Washita Region, Crop Irrigation and Public Supply demands will increase while Self-supplied Domestic and Livestock demands will decrease between 2020 and 2075. There is no change in Oil & Gas and Self-supplied Industrial demands. There are no Thermoelectric Power demands.

Total Demand by Sector (AFY)

	2020	2030	2035	2045	2060	2075
Self-supplied Domestic	3,425	3,484	3,459	3,414	3,371	3,347
Self-supplied Industrial	31	31	31	31	31	31
Crop Irrigation	10,501	11,806	11,806	11,923	12,390	13,156
Livestock	8,248	8,030	8,010	7,818	7,551	7,330
Oil & Gas	6,639	6,639	6,639	6,639	6,639	6,639
Public Supply	33,172	34,153	34,076	33,966	34,319	34,476
Thermoelectric Power	-	-	-	-	-	-
Total	62,015	64,141	64,021	63,791	64,300	64,980

AFY = acre-feet per year; Small differences may result due to rounding.

Physical Water Shortages WW WM WSS

To quantify physical surface water gaps and groundwater storage depletions through 2075, use of existing surface water and groundwater supplies was assumed to continue in current proportions while out-of-basin supplies will be used up to permit amounts or projected demands, whichever is less.

The Lower Washita Region is projected to experience Surface Water gaps (where demand exceeds supplies) and Groundwater depletions (where water use exceeds the rate of recharge), as detailed in the tables below. The magnitude of shortages is projected for all planning years, and the frequency (probability) of a shortage occurring is estimated for 2075 demand conditions. Bedrock groundwater frequencies are constant because of the lack of direct connection to surface water hydrology. Frequent shortages with large magnitudes are indicative of the greatest need to implement alternative water management strategies.

SURFACE WATER GAP	2030	2035	2045	2060	2075	2075
	Maximum Magnitude (AFY)					Frequency
Basin						
14	24	6	1	1	1	1%
15	2	-	-	-	-	0%
16	2	1	-	-	-	0%
21	-	-	-	-	-	0%
22	24	28	25	46	55	6%
23	18	17	10	4	-	8%

AFY = acre-feet per year

ALLUVIAL GROUNDWATER DEPLETION	2030	2035	2045	2060	2075	2075
	Maximum Magnitude (AFY)					Frequency
Basin						
14	7	7	-	-	-	0%
15	-	-	-	-	-	0%
16	-	-	-	-	-	0%
21	-	-	-	-	-	0%
22	9	9	9	9	9	6%
23	-	-	-	-	-	No AGW Demand

AFY = acre-feet per year

BEDROCK GROUNDWATER DEPLETION	2030	2035	2045	2060	2075
	Average Magnitude (AFY)				
Basin					
14	47	47	45	41	36
15	43	35	28	27	29
16	87	87	60	23	7
21	25	26	25	24	24
22	10	10	10	9	8
23	19	18	16	12	10

AFY = acre-feet per year



Surface Water Resources

WIW WM WSS WDI

The OCWP uses historical monthly streamflow data (1950-2021), which reflects current natural and human-created conditions (runoff, diversions and use of water, and impoundments and reservoirs) to represent the water that may be physically available to meet projected demand. The maximum amount of water a reservoir can dependably supply during a critical drought period is referred to as its yield. The table below provides information about remaining water supply yield that is available for permitting from existing reservoirs in the region.

Reservoir	Estimated Remaining Water Supply Yield to be Permitted (AFY)
Arbuckle	0
Clear Creek	---
Duncan	---
Elmore City Lake	0
Fuqua	2,182
Humphreys	0
Jean Neustadt	883
Pauls Valley	---
RC Longmire	0
Rock Creek Reservoir	0
Taylor	---
Wiley Post Memorial	0
Chickasha	---
Murray	0
Texoma	50,091
Heraldton	1,527

--- Indicates no information is available.
 AFY = acre-feet per year
 Estimated remaining water supply yield as of July 2025.

Legal Water Availability WM WSS


Surface water and groundwater are projected to remain legally available for permitting through 2075 in all of the basins within the Lower Washita Region basins. Permitting of surface water in portions or all of Lower Washita Region basins is subject to provisions of the 2016 Water Settlement Agreement.

Surface Water Legal Availability

- Planning Basins
- Basins under GRDA authority
- Basins wholly or partially subject to the provisions of the 2016 Water Settlement Agreement

Surface Water Legal Availability (AFY) using 2075 Demands


- 0
- <200,000
- 200,001-500,000
- 500,001-2,000,000
- 2,000,001-4,000,000
- >4,000,000



Groundwater Legal Availability

- Planning Basins
- #### Groundwater Legal Availability (AFY) using 2075 Demands

- <200,000
- 200,001-500,000
- 500,001-2,000,000
- 2,000,001-4,000,000
- >4,000,000



Legal water availability projected in 2075 varies across the region, with darker shading indicating more water available for appropriation.

Groundwater Resources

WW WM WSS WDI

For the OCWP physical water availability analyses, alluvial aquifers are defined as aquifers comprised of river alluvium and terrace deposits, occurring along rivers and streams and consisting of unconsolidated deposits of sand, silt, and clay. Alluvial aquifers are more hydrologically connected with surface water features (streams, rivers, lakes) than bedrock aquifers. Bedrock aquifers consist of consolidated (solid) or partially consolidated rocks, such as sandstone, limestone, dolomite, and gypsum. Bedrock aquifers are typically replenished slowly by recharge from surface infiltration (precipitation) and from adjacent aquifers.

Aquifer	Type	Class	Equal Proportionate Share (AFY/Acre)
Antlers	Bedrock	Major	2.1
Arbuckle-Simpson	Bedrock	Major	0.2
Canadian River	Alluvial	Major	temporary 2.0
El Reno	Bedrock	Minor	temporary 2.0
Gerty Sand	Alluvial	Major	0.65
Marietta	Bedrock	Minor	temporary 2.0
Red River Reach 2	Alluvium and Terrace	Major	temporary 2.0
Red River Reach 3	Alluvium and Terrace	Major	temporary 2.0
Rush Springs	Bedrock	Major	temporary 2.0
Texoma	Bedrock	Minor	temporary 2.0
Washita River Reach 3	Alluvium and Terrace	Major	1.5
Washita River Reach 4	Alluvium and Terrace	Major	1.0
Woodbine	Bedrock	Minor	temporary 2.0

AFY = acre-feet per year

Bedrock aquifers with typical yields greater than 50 gallons per minute (gpm) and alluvial aquifers with typical yields greater than 150 gpm are considered major aquifers.

Water Quality WW WDI



Groundwater: Groundwater from the major aquifers such as the Arbuckle-Simpson, Antlers, and Rush Springs has an assortment of water quality concerns involving elevated nitrate, total dissolved solids, and salinity concentrations. The lack of seasonal data, especially in sensitive karst systems, makes it difficult to track changes in water quality over time.



Lakes: Water quality in this region is impacted by elevated levels of nutrients, chlorophyll-a, and turbidity—factors that directly affect both recreational and water supply uses. Fifteen out of eighteen lakes in the region are impacted by elevated nutrient levels and are classified as eutrophic. Excess nutrients and productivity increase the risk of harmful algal blooms (HABs), which contribute to higher water treatment costs, taste and odor issues, and reduced recreational value—ultimately affecting both water supply and recreational uses.



Streams: Rivers and streams are impacted by erosion, drought-flood cycling, increased sedimentation, and increased nutrient concentrations. These factors contribute to poor aesthetics, habitat degradation, water insecurity, and increased treatment costs.

Water Infrastructure Needs WIW

OWRB compiled near-term wastewater project needs, water supply project needs, and state flood plan project needs as part of developing the 2025 OCWP. Near-term costs include drinking water and wastewater projects by public utilities (various system sizes) and other entities (such as conservancy districts, department of wildlife, regional councils, and tourism). All flood mitigation projects in the database were identified by public water suppliers in the State Flood Plan.

Near-term Drinking Water Cost (2024 dollars)	Near-term Wastewater Cost (2024 dollars)	Near-term Stormwater Cost (2024 dollars)
\$870M	\$415M	\$24M

M = million

For drinking water, costs were projected for the next 20 years for public suppliers. While it is difficult to anticipate all the changes that may occur within this extended timeframe, it is beneficial to evaluate the order of magnitude of the long-range potential costs of meeting demands. Estimated costs include rehabilitation of existing water infrastructure and construction of new water infrastructure for growth and regulatory compliance. The costs are categorized according to system sizes:

- Small systems serve less than 3,300 people;
- Small-medium systems serve 3,301 to 10,000 people;
- Medium-large systems serve 10,001-100,000 people; and
- Large systems serve more than 100,000 people.

System Size	Near-term Drinking Water Cost (2024 dollars)	Future Drinking Water Costs through 2035 (2025 dollars) ¹	Future Drinking Water Costs through 2045 (2025 dollars) ²
Small	\$60M	\$742M	\$534M
Small-Medium	\$297M	\$1.06B	\$2.33B
Medium-Large	\$212M	\$697M	\$674M
Large	N/A	N/A	N/A
Non-Public suppliers	\$300M	N/A	N/A
Total	\$870M	\$2.50B	\$3.53B

M = million; B = billion; N/A = not applicable

1. Not inclusive of near-term costs.

2. Not inclusive of near-term or future drinking water costs through 2035.

Visit OWRB Water Planning page (<https://oklahoma.gov/owrb/water-planning.html>) for more information on region water quality and trend analysis.